DATA SHEET 1(3)



# PORTABLE MULTI GAS DETECTOR GasAlertMicroClip XL

PART. NR. 1160403-1160406

PORTABLE GAS DETECTOR LEL, O, H,S, CO

## **GENERAL INFORMATION**

- Multi-gas detector up to 4 gasses
- Compact and light weight (190 gram)
- Visual, acoustic and vibration alarms
- ATEX / IECEx certified
- Display with backlight
- One button operation
- Schock resistant housing

## Multi-gas made easy

The **GasAlertMicroClip XL**offers the versatility of a multigas detector with the simplicity of a single button. This thin and compact multigas detector is suitable for the detection of oxygen, toxic and flammable gases. Before the occurrence of an unsafe situation, the detector gives an alarm by means of a powerful acoustic signal, intense red flashing LED display including a vibrating alarm. Hear, see and feel!

### User friendly

The **GasAlertMicroClip XL** is composed of a durable shockproof housing and is water resistant. The sturdy alligator carrying clip ensures that this thin multi-gas detector is firmly attached to the work clothing. The operation is simple by means of one push button. The gas concentration per sensor can be read continuously on the large and clear LC display. The rechargeable lithium polymer battery offers a long service life, continuity and it's recharged in less than 6 hours.

#### Wide range of applications

Thanks to its compact design, easy handling and a light weight of approximately 190 grams, the **GasAlertMicroClip XL** is a very user-friendly safety instrument. Useable in heavy industry environments, including Petrochemicals, Offshore, Soil remediation, Shipping, Water purification, Fire Brigade and many other industries!

#### **APPLICATIONS:**

- Chemical Industry
- Refineries
- ⊕ Waste water treatment
- Boiler houses
- Confined spaces (and entry to)
- Storage of dangerous goods
- Food industry

#### CONSILIUM DOES MORE THAN JUST DELIVER!

- 1 Tailor made advice
- Project management
- 1 Technical support
- Training and education
- Commissioning
- ① Onsite service / maintenance / calibration
- Rentals

The specifications described herein are subject to change without notice

DATA SHEET GASALERTMICROCLIP XL\_1160403-1160406\_EN\_v2.00



# ORDERING INFORMATION

PORTABLE MULTI GAS DETECTOR							
VERSION	PART.NO.	GAS TYPE(S)	MEASURING RANGE	LOW ALARM	HIGH ALARM		
GasAlertMicro Clip XL LEL, O <sub>2</sub>	1160406	CH <sub>4</sub> Methane Oxygen	0-100% 0-30 Vol%	10 %LEL 19.5 Vol%	20 %LEL 23.5% Vol%		
GasAlertMicro Clip XL LEL, O <sub>2,</sub> H <sub>2</sub> S	1160403	CH₄ Oxygen Hydrogen Sulphide	0-100% 0-30 Vol% 0-100ppm	10%LEL 19.5Vol% 1.6 ppm	20 %LEL 23.5 Vol% 2.4 ppm		
GasAlertMicro Clip XL LEL, O <sub>2</sub> , CO	1160404	CH₄ Methane Oxygen Carbon Monoxide	0-100% 0-30 Vol% 0-500ppm	10%LEL 19.5Vol% 25 ppm	20 %LEL 23.5 Vol% 50 ppm		
$\begin{array}{l} \text{GasAlertMicro Clip XL} \\ \text{LEL, } O_{2}, \text{CO, H}_{2}\text{S} \end{array}$	1160405	CH₄ Methane Oxygen Carbon Monoxide Hydrogen Sulphide	0-100% 0-30 Vol% 0-500ppm 0-100ppm	10%LEL 19.5Vol% 25 ppm 1.6 ppm	20 %LEL 23.5 Vol% 50 ppm 2.4 ppm		

ACCESSOIRES					
ТҮРЕ	IMAGE	PART. NO.	DESCRIPTION		
Sensor protection		1160462	Auxiliary filter kit (complete with filter adaptor and 5 filters)		
Multi-Unit Power adaptor	70 S	1160415	simultaneously charges 5 detectors		
Car power adapter		1160420	12-24 VDC vehicle power adaptor (for cigarette lighter)		
Test gas	u.e.	9990518	Test gas cylinder (mixture) CH <sub>4</sub> , H <sub>2</sub> S, CO, O <sub>2</sub> in N <sub>2</sub> , 58 gas litre		
Regulator		9990600	Regulator for gas cylinder, fixed flow		

The specifications described herein are subject to change without notice.





# **SPECIFICATIONS**

PRODUCT	GASALERTMICROCLIP XL
Dimensions	11.3 × 6.0 × 3.1 cm
Weight	190 grams
Housing	IP68 – up to 45 minutes at 1.2 mtr depth
Measuring principle	Catalytic (LEL) and/or Electrochemical (toxic and oxygen)
Battery	Lithium (typical: 18 hrs life time and 6 hrs recharging)
Operating temperature	-20°C tot +50°C
Humidity	0-95% RH non condensing
Display	LCD-display Bright, intuitive wide-angle visual alarm bars incl. icons
Alarm	see ordering information
Alarm indicators	Visual, vibrating, audible (95 dB)
(over limit)	Low, High, TWA, STEL, OL
EEx-classification	ATEX II I G Ex ia IICT4 Ga // CSA Class I, Div. I , Gr. A, B, C, D
Certificate	IECEx Ex ia IICT4 Ga
Manufacturer	OEM BW







